

COATING *Solutions*



CONVERTER COAT

Rust Conversion Aerosol



- Seals surface to prevent rust and corrosion
- Converts rust into a polymeric black coating
- Neutralizes existing rust

S **tate**[®]
Since 1911

CARE FOR WORK ENVIRONMENTS[®]

CONVERTER COAT

Rust Conversion Aerosol

STOPS EXISTING RUST

This unique formula effectively neutralizes existing rust and converts it to a protective black, polymeric coating.

PREVENTS NEW RUST FROM FORMING

Once dry, this black organic coating seals out rust-causing moisture and oxygen, providing a long lasting, rust-free surface.

WEATHER RESISTANT

Converter Coat's tough finish helps protect metals against rain, sleet, snow, wind, humidity, rock salt, acid rain, smog and other corrosive conditions.

EASY APPLICATION

No brushing, rolling or dipping. Just wire brush away loose rust, aim Converter Coat and spray. Converter Coat's smooth, black finish is ready to be painted over without tedious surface preparations.

DIRECTIONS FOR USE:

It is not necessary to remove all rust before applying Converter Coat. Simply remove loose rust and paint with a wire brush prior to application. For best results, clean the metal surface with a product, such as State 999® or SSD II, prior to applying Converter Coat to remove contaminants such as grease, oil or wax from the surface. Be sure surface is dry and completely free of water.

Shake the can well and hold it 10-12 inches from the surface to be coated. Spray Converter Coat in even strokes over the surface. Converter Coat may initially appear white, but will turn black as it reacts with the rusted surface to form a protective coating.

For maximum performance apply when the temperature is between 50°F and 95°F. Allow 3-5 minutes drying time between coats. Two coats are recommended. Allow 48 hours before applying paint to surface.

Invert can and spray to clear nozzle and prevent clogs after each use.

TECHNICAL DATA:

APPEARANCE: clear coating - turns rust black

COLOR: black on rusted metal

ODOR: solvent

COMPOSITION: acrylic

FLAMMABILITY: 65°F (TCC)

DRY TIME: to touch: 15-20 minutes

hard: 1 hour

RECOAT: after 3-5 hours

SHELF LIFE: one year minimum

PACKAGING

121925-12 10 OZ Aerosol/CS12
121925-24 10 OZ Aerosol/CS24



State Industrial Products
5915 Landerbrook Drive
Mayfield Heights, OH 44124
To Order Call: 1-866-747-2229
www.stateindustrial.com

Canada
6935 Davand Drive
Mississauga, Ontario L5T 1L5
To Order Call: 1-800-668-6513

Puerto Rico
Royal Industrial Park, Bldg "M"
Local #5, Carr 869, km 1.5 Palmas
Cataño, P.R. 00962
To Order Call: 787-275-3185